









JD-10080

JD-10080 X射线是一种可以穿透木材、纸板、皮革等不透明物体的电磁波。安检仪能根据物体对X射线的吸收程度，在荧屏上呈现不同颜色的影像。简单来说，橙色代表有机物，例如食品、塑料等；书本、陶瓷等显示为绿色；金属则显示为蓝色。这时，安检员快速查看X射线扫描的透视图像，就能凭借丰富的经验判断是否有违禁品。

JD-10080 X-rays are electromagnetic waves that can penetrate opaque objects such as wood, cardboard and leather. The screening device can present different color images on the screen according to the degree of absorption of X-rays by the object. Simply put, orange represents organic materials, such as food and plastics; books and ceramics are shown in green; and metals are shown in blue. At this point, the security inspector quickly checks the X-ray scanning fluoroscopic image, and will be able to rely on extensive experience to determine whether there is any contraband.

技术规格Technical specifications

型号Model	JD-10080
通道尺寸Channel Size	1000*800mm
传送带速度Conveyor speed	0.22m/s
传送带额走负荷conveyor belt front loading	180kg
穿透力penetrating force	底视角≥47mm 钢板 Bottom View:≥47mm　侧视角≥47mm钢板 Steel Plate Side View:≥47mm Steel Plate
穿透分辨力power of penetration and discrimination	底视角≥0.127mm Bottom Viewing Angle:≥0.127mm　侧视角≥0.127mm Side Viewing Angle:≥0.127mm
空间分辨力spatial resolution	底视角:三0.8mm Bottom Viewing Angle:Three 0.8mm　侧视角:三0.8mm Side Viewing Angle:Three 0.8mm
胶卷支全性film integrity	对IS01600胶卷安全 Safe for IS01600 film
工作温度/湿度Operating Temperature/Humidity	0℃-45℃/20-95%(不冷凝) 0°C-45°C/20-95% (non-condensing)
工作电压operating voltage	220VAC±10%)　50±3HZ
功率损耗power loss	0.8KW(最大值) 0.8KW (maximum)
噪声级voice level	<48dB
国际名牌配件International brand accessories	美国 SPELLMAN 射线源，日本，HAMMATSU探测器，德国 INTERROLL 滚筒， SPELLMAN radiation source, USA; HAMMATSU detector, Japan; INTERROLL drum, Germany.
一键关机控制One-touch shutdown control	关机时只需旋转一下钥匙，设备自动安全关机，减少设备故障。 Simply turn the key when shutting down and the unit automatically shuts down safely, reducing equipment failure.
动态画面切换Motion picture switching	画面在静止的时候可以切换，在动态的时候也可以自如切换。 The screen can be switched when it's still, and it can be switched freely when it's in motion.
报警方式Alarm Methods	满足条件时发出声音和报警灯信号 Sound and alarm light signals when conditions are met

特殊尺寸可按照客户要求定　特殊尺寸可按照客户要求定制 Special sizes can be customized according to customer requireme...

诚信源于专业 实力来自积累 Honesty comes from professionalism Strength comes from accumulation











JD-100100

JD-100100安检机，又名安检仪，包括安检X光机，行李安检机，通道式X光机，物检X光机，X射线安检仪，X光行李安检机，X射线检测仪，X射线异物检测机，X光安检机，X光行包检测仪，三品检测仪，三品检查机，三品检查仪，查危仪。
安检机广泛应用于机场、火车站、地铁站、汽车站、政府机关大楼、大使馆、会议中心、会展中心、酒店、商场、大型活动、邮局、学校、物流行业、工业检测等。

JD-100100 security screening machine, also known as security checker, including security X-ray machine, baggage screening machine, channel X-ray machine, physical inspection X-ray machine, X-ray security checker, X-ray baggage screening machine, X-ray detector, X-ray foreign object detector, X-ray security machine, X-ray traveling bag detector, three goods detector, three goods inspection machine, three goods inspection machine, checking the danger of the machine.
Security check machines are widely used in airports, railway stations, subway stations, bus stations, government buildings, embassies, conference centers, convention centers, hotels, shopping malls, large-scale events, post offices, schools, logistics industry, industrial inspection and so on.

技术规格Technical specifications

型号Model	JD-100100
通道尺寸Channel Size	1000*1000mm
传送带速度Conveyor speed	0.22m/s
传送带额走负荷conveyor belt front loading	180kg
穿透力penetrating force	底视角≥47mm 钢板 Bottom View:≥47mm　侧视角≥47mm钢板 Steel Plate Side View:≥47mm Steel Plate
穿透分辨力power of penetration and discrimination	底视角≥0.127mm Bottom Viewing Angle:≥0.127mm　侧视角≥0.127mm Side Viewing Angle:≥0.127mm
空间分辨力spatial resolution	底视角:三0.8mm Bottom Viewing Angle:Three 0.8mm　侧视角:三0.8mm Side Viewing Angle:Three 0.8mm
胶卷支全性film integrity	对IS01600胶卷安全 Safe for IS01600 film
工作温度/湿度Operating Temperature/Humidity	0℃-45℃/20-95%(不冷凝) 0°C-45°C/20-95% (non-condensing)
工作电压operating voltage	220VAC±10%)　50±3HZ
功率损耗power loss	0.8KW(最大值) 0.8KW (maximum)
噪声级voice level	<48dB
国际名牌配件International brand accessories	美国 SPELLMAN 射线源，日本，HAMMATSU探测器，德国 INTERROLL 滚筒， SPELLMAN radiation source, USA; HAMMATSU detector, Japan; INTERROLL drum, Germany.
一键关机控制One-touch shutdown control	关机时只需旋转一下钥匙，设备自动安全关机，减少设备故障。 Simply turn the key when shutting down and the unit automatically shuts down safely, reducing equipment failure.
动态画面切换Motion picture switching	画面在静止的时候可以切换，在动态的时候也可以自如切换。 The screen can be switched when it's still, and it can be switched freely when it's in motion.
报警方式Alarm Methods	满足条件时发出声音和报警灯信号 Sound and alarm light signals when conditions are met

特殊尺寸可按照客户要求定制 Special sizes can be customized according to customer requirements







JD-5030

JD-5030采用X光扫描成像技术，通过对物品进行扫描，并输出影像以供检查人员判断是否夹带违禁品，拥有清晰的成像效果，借助多项图像处理功能，能简单、快速地辅助检查人员辨别区分不同物质。 扫描成像过程中，系统提供自动图像存储和由检查人员根据工作需要自行存储两种方式。

JD-5030 adopts X-ray scanning and imaging technology, by scanning the articles and outputting images for inspectors to judge whether the contraband is contained or not, it has clear imaging effect, and with the help of a number of image processing functions, it can easily and quickly assist inspectors to recognize and distinguish different substances. During the scanning and imaging process, the system provides two ways of automatic image storage and storage by the inspectors themselves according to their work needs.

技术规格Technical specifications

型号Model	JD-5030
通道尺寸Channel Size	500*300mm
传送带速度Conveyor speed	0.22m/s
传送带额走负荷conveyor belt front loading	180kg
穿透力penetrating force	底视角:≥47mm 钢板 Bottom View:≥47mm　侧视角:≥47mm钢板 Steel Plate Side View:≥47mm Steel Plate
穿透分辨力power of penetration and discrimination	底视角:≥0.127mm Bottom Viewing Angle:≥0.127mm　侧视角:≥0.127mm Side Viewing Angle:≥0.127mm
空间分辨力spatial resolution	底视角:三0.8mm Bottom Viewing Angle:Three 0.8mm　侧视角:三0.8mm Side Viewing Angle:Three 0.8mm
胶卷支全性film integrity	对IS01600胶卷安全 Safe for IS01600 film
工作温度/湿度Operating Temperature/Humidity	0°C-45°C/20-95%(不冷凝) 0°C-45°C/20-95% (non-condensing)
工作电压operating voltage	220VAC±10%)　50±3HZ
功率损耗power loss	0.8KW(最大值) 0.8KW (maximum)
噪声级voice level	<48dB
国际名牌配件International brand accessories	美国 SPELLMAN 射线源，日本，HAMMATSU探测器，德国 INTERROLL 滚筒， SPELLMAN radiation source, USA; HAMMATSU detector, Japan; INTERROLL drum, Germany.
一键关机控制One-touch shutdown control	关机时只需旋转一下钥匙，设备自动安全关机，减少设备故障， Simply turn the key when shutting down and the unit automatically shuts down safely, reducing equipment failure.
动态画面切换Motion picture switching	画面在静止的时候可以切换，在动态的时候也可以自如切换。 The screen can be switched when it's still, and it can be switched freely when it's in motion.
报警方式Alarm Methods	满足条件时发出声音和报警灯信号 Sound and alarm light signals when conditions are met

特殊尺寸可按照客户要求定制 Special sizes can be customized according to customer requirem

诚信源于专业 实力来自积累 Honesty comes from professionalism Strength comes from accumulation








JD-6550

JD-6550 X射线是一种可以穿透木材、纸板、皮革等不透明物体的电磁波。安检仪能根据物体对X射线的吸收程度，在荧屏上呈现不同颜色的影像。简单来说，橙色代表有机物，例如食品、塑料等；书本、陶瓷等显示为绿色；金属则显示为蓝色。这时，安检员快速查看X射线扫描的透视图像，就能凭借丰富的经验判断是否有违禁品。

JD-6550 X-rays are electromagnetic waves that can penetrate opaque objects such as wood, cardboard and leather. The screening device can present different color images on the screen according to the degree of absorption of X-rays by the object. Simply put, orange represents organic materials, such as food and plastics; books and ceramics are shown in green; and metals are shown in blue. At this point, the security inspector quickly checks the X-ray scanning fluoroscopic image, and will be able to rely on extensive experience to determine whether there is any contraband.

技术规格Technical specifications

型号Model	JD-6550
通道尺寸Channel Size	650*500mm
传送带速度Conveyor speed	0.22m/s
传送带额走负荷conveyor belt front loading	180kg
穿透力penetrating force	底视角:≥47mm 钢板 Bottom View:≥47mm　侧视角:≥47mm钢板 Steel Plate Side View:≥47mm Steel Plate
穿透分辨力power of penetration and discrimination	底视角:≥0.127mm Bottom Viewing Angle:≥0.127mm　侧视角:≥0.127mm Side Viewing Angle:≥0.127mm
空间分辨力spatial resolution	底视角:三0.8mm Bottom Viewing Angle:Three 0.8mm　侧视角:三0.8mm Side Viewing Angle:Three 0.8mm
胶卷支全性film integrity	对IS01600胶卷安全 Safe for IS01600 film
工作温度/湿度Operating Temperature/Humidity	0°C-45°C/20-95%(不冷凝) 0°C-45°C/20-95% (non-condensing)
工作电压operating voltage	220VAC±10%)　50±3HZ
功率损耗power loss	0.8KW(最大值) 0.8KW (maximum)
噪声级voice level	<48dB
国际名牌配件International brand accessories	美国 SPELLMAN 射线源，日本，HAMMATSU探测器，德国 INTERROLL 滚筒， SPELLMAN radiation source, USA; HAMMATSU detector, Japan; INTERROLL drum, Germany.
一键关机控制One-touch shutdown control	关机时只需旋转一下钥匙，设备自动安全关机，减少设备故障， Simply turn the key when shutting down and the unit automatically shuts down safely, reducing equipment failure.
动态画面切换Motion picture switching	画面在静止的时候可以切换，在动态的时候也可以自如切换。 The screen can be switched when it's still, and it can be switched freely when it's in motion.
报警方式Alarm Methods	满足条件时发出声音和报警灯信号 Sound and alarm light signals when conditions are met

根客户要求定制 Special sizes can be customized according to customer requirements